





















Série	Modèle	Profondeur		Degré de la lame	c/c des lames		% d'air libre*	Surface libre*		Épaisseur de la lame		Poids au pi ²	Profil de la lame
		mm	"		mm	"		m ²	pi ²	mm	"		
Série 100 Lames standard	101-35R	38,1 mm	1½"	35°	25 mm	1"	48,88%	0,726 m ²	7,820 pi ²	1,60 mm	0,063"	3,19 lbs	
	101-45	38,1 mm	1½"	45°	41 mm	1½"	37,94%	0,564 m ²	6,070 pi ²	1,30 mm	0,051"	2,06 lbs	
	102-45	50,8 mm	2"	45°	64 mm	2½"	39,82%	0,592 m ²	6,370 pi ²	1,60 mm	0,063"	2,31 lbs	
	104-30	101,6 mm	4"	30°	76 mm	3"	54,42%	0,809 m ²	8,710 pi ²	1,60 mm	0,063"	2,63 lbs	
	104-45	101,6 mm	4"	45°	102 mm	4"	49,79%	0,740 m ²	7,970 pi ²	1,80 mm	0,071"	2,82 lbs	
	106-45	152,0 mm	6"	44°	152 mm	6"	51,38%	0,764 m ²	8,220 pi ²	3,17 mm	0,125"	4,23 lbs	
Série 200 Lames anti-infiltrations	201-30	25,4 mm	1"	30°	38 mm	1½"	32,77%	0,487 m ²	5,240 pi ²	1,60 mm	0,063"	2,33 lbs	
	202-45	50,8 mm	2"	37°	71 mm	2¾"	34,42%	0,510 m ²	5,490 pi ²	1,60 mm	0,063"	2,33 lbs	
	204-30	101,6 mm	4"	30°	95 mm	3¾"	48,14%	0,716 m ²	7,700 pi ²	1,60 mm	0,063"	3,03 lbs	
	204-37	101,6 mm	4"	37°	112 mm	4½"	46,48%	0,691 m ²	7,440 pi ²	1,90 mm	0,075"	2,83 lbs	
	204-45	101,6 mm	4"	45°	127 mm	5"	49,30%	0,732 m ²	7,880 pi ²	1,65 mm	0,081"	2,53 lbs	
	204-45-3	101,6 mm	4"	45°	127 mm	5"	49,30%	0,732 m ²	7,880 pi ²	3,00 mm	0,118"	3,40 lbs	
	206-45	152,0 mm	6"	45°	146 mm	5¾"	47,06%	0,700 m ²	7,530 pi ²	2,06 mm	0,081"	2,06 lbs	
Série 400 Lame en "V"	404-V	101,6 mm	4"	59°	102 mm	4"	33,86%	0,503 m ²	5,420 pi ²	1,98 mm	0,078"	3,54 lbs	
	404-40	101,6 mm	4"	40°	76 mm	3"	44,47%	0,661 m ²	7,110 pi ²	2,06 mm	0,081"	4,16 lbs	
Série D Lames drainables	104-35D	101,6 mm	4"	35°	89 mm	3½"	54,08%	0,804 m ²	8,650 pi ²	2,06 mm	0,081"	3,43 lbs	
	104-45D	101,6 mm	4"	45°	89 mm	3½"	51,78%	0,770 m ²	8,290 pi ²	2,06 mm	0,081"	3,44 lbs	
	106-35D	152,0 mm	6"	35°	89 mm	3½"	63,66%	0,946 m ²	10,180 pi ²	2,06 mm	0,081"	4,31 lbs	
	106-45DD	152,0 mm	6"	45°	146 mm	5¾"	46,10%	0,680 m ²	7,370 pi ²	2,06 mm	0,081"	3,95 lbs	
	404-40D	101,6 mm	4"	45°	70 mm	2¾"	46,40%	0,690 m ²	7,420 pi ²	2,06 mm	0,081"	3,63 lbs	

* Ces données ne tiennent pas compte du grillage